

Electric pedestrian stacker EJC B12 / B14 / B16 / B20

Lift height: 2500-5350 mm / Load capacity: 1200-2000 kg





The sturdy stacker for flexible requirements.

Safely moving special and euro pallets.

The flexible and efficient pedestrian stackers EJC of the B series are specifically designed for the handling of special goods. Their support arms are laterally offset and their forged forks can be lowered completely to the ground. This makes it possible to pick up load units from below. The forks are also available in different variations.

The pedestrian stackers are equipped with a powerful 3-phase AC motor, which due to its quick acceleration ensures efficient working conditions in your warehouse. The lift motor, too, convinces with its strong performance and still is surprisingly quiet. It allows – in combination with the optimised hydraulics – for particularly gentle and precise stacking. Thus, the lift motor also contributes to fatigue-free and safe working.

Reliable availability is provided by the optionally built-in charger, which charges the long-lasting batteries at any regular 230-V outlet.



5 years carefree. Guaranteed.

Extremely fast charging times and zero maintenance make liion batteries by far the most enduring energy source. With our 5-year guarantee on li-ion batteries, we give you a longterm performance promise, regardless of operating hours.



100% satisfaction. Guaranteed.

We are convinced our lithium-ion technology is right for you. That's why we guarantee that you can easily and quickly switch back to the technology you originally used at any time within the first 6 months after delivery – without giving reasons.

All benefits at a glance:

- Powerful and maintenance-free 3-phase AC motors
- Pick-up of closed or transverse pallets
- Proportional hydraulics for precise and gentle depositing and lifting
- Safe crawl speed with upright tiller
- Individual adaptation for wide-ranging applications

Overview

The right solution for your applications:

Name	Load capacity/ load	Lift height (max.)	Travel speed un- laden	Aisle width (pal- let 800x1200 length)	Lift speed un- laden
EJC B12	1200 kg	4700 mm	6 km/h	2247 mm	0.22 m/s
EJC B14	1400 kg	5350 mm	6 km/h	2352 mm	0.25 m/s
EJC B16	1600 kg	5250 mm	6 km/h	2352 mm	0.25 m/s
EJC B20	2000 kg	4800 mm	6 km/h	2352 mm	0.18 m/s

The German production facilities in Norderstedt, Moosburg and Landsberg are certified.



